

Product Data Sheet

Eastman Cellulose Acetate Butyrate (CAB-551-0.2)

Application/Uses

- Automotive OEM
- Coatings for Automotive Plastics
- Coatings for automotive
- Coatings for plastic
- Coatings
- Nail care
- Truck/Bus/Commercial Vehicles

Product Description

Eastman Cellulose Acetate Butyrate (CAB-551-0.2) is a cellulose ester with high butyryl content and relatively low molecular weight. It is compatible with numerous cross-linking resins and has a lower solution viscosity. In coatings, Eastman CAB-551-0.2 gives clear films, reduces surface tack and mottling, minimizes cratering, improves flow and thermal reflow, and provides intercoat adhesion and good UV stability. It is useful for durable cross-linked formulations. Its good compatibility with a wide range of curing resin systems and its solubility in a wide variety of solvents and solvent combinations make it useful as an additive in numerous coating compositions.

Typical Properties

Butyryl Content	52 wt %
Acetyl Content	2 wt %
Hydroxyl Content	1.8%
Viscosity ^a	0.76 poise
Color ^b	50 ppm
Haze ^b	15 ppm
Acidity as Acetic Acid	0.02 wt %
Ash Content	<0.05%
Refractive Index	1.475
Melting Point	130-140°C
Glass Transition Temperature (T _g)	101°C
Specific Gravity	1.16
Wt/Vol	1.16 kg/L (9.67 lb/gal)
Bulk Density	
Poured	515 kg/m ³ (32 lb/ft ³)
Tapped	612 kg/m ³ (38 lb/ft ³)
Dielectric Strength	787-984 kv/cm (2-2.5 kv/mil)
Molecular Weight ^c M _n	30000
Tukon Hardness	15 Knoop

Comments

Properties reported here are typical of average lots. Eastman makes no representation that the material in any particular shipment will conform exactly to the values given.